

## Cat.7 10G S/FTP PVC Patch Cord Round Cable

Opternet Patch Cords have been designed for high speed data transmission over local area networks (LANs) and for Gigabit Ethernet 1000 Mbps applications. These cables exceed performance requirements specified by the TIA/EIA-568B.2 / TIA/EIA-568C.2 and IEC 60603-7-4 standards. Opternet cables are ideal for simple, cost-effective and high-speed transmission performance. They support a higher signal- to - noise ratio, providing better reliability for current applications and higher data rates for future applications. These Patch Cords comprise of a flexible patch cable and terminating with two modular plugs along with molded boots.

<b>Make</b>	<b>OPTERNET</b>
Type	Patch Cord
Pairs	4

### Applications

- Patch Work and Work Area
- 4/16 Mbps Token Ring (IEEE 802.5)
- 10/100/1000 Base/10G BaseT (IEEE 802.3)
- 155Mbps ATM
- 100 Mbps TP-PMD
- Analogue Voice, ISDN, ADSL



### Specifications

- Insulation Material: HDPE
- Conductor and Metal: 7 Bare Copper Wires, 24 AWG
- Jacket: PVC
- Plugs: RJ-45 8P8C
- Contact : Gold plated: 30µ
- Contact blade: Phosphor Bronze
- Molded Boot: PVC
- Fire Resistant: CMG Specifications
- Cable Shield : Aluminum Mylar

### Standards

- ISO/IEC11801:2011 (Ed. 2.2)
- ANSI/TIA/EIA-568-C.2
- EN 50173-1:2011
- EN 50173-2:2007 including amendment A1:2010
- IEC61935-2:2010 (Ed.3.0)
- ROHS Compliant

### Ordering Information

Part No.	Description
OLC7PC1MSFTP GREY-LSZH	Cat.7 10G S/FTP PVC Patch Cord Round Cable

\* Replace XX with - Grey (GL), Blue (BL), White (WH), Red (RD), Black (BK), Green (GR) or Yellow (YL) Colour.

\* Replace YY with 0.5m, 1.0m, 2.0m, 3.0m, 5.0m,.....10m...15m...30..... meters etc. length